

54/7406

HEX INVERTER BUFFER/DRIVER
(With Open-Collector High-Voltage Output)


ORDERING CODE: See Section 9

PKGS	PIN OUT	COMMERCIAL GRADE	MILITARY GRADE	PKG TYPE
		$V_{CC} = +5.0\text{ V} \pm 5\%$, $T_A = 0^{\circ}\text{C to } +70^{\circ}\text{C}$	$V_{CC} = +5.0\text{ V} \pm 10\%$, $T_A = -55^{\circ}\text{C to } +125^{\circ}\text{C}$	
Plastic DIP (P)	A	7406PC		9A
Ceramic DIP (D)	A	7406DC	5406DM	6A
Flatpak (F)	A	7406FC	5406FM	3I

INPUT LOADING/FAN-OUT: See Section 3 for U.L. definitions

PINS	54/74 (U.L.) HIGH/LOW
Inputs	1.0/1.0
Outputs	OC**/10

CONNECTION DIAGRAM
PINOUT A



DC AND AC CHARATERISTICS: See Section 3*

SYMBOL	PARAMETER		54/74		UNITS	CONDITIONS	
			Min	Max			
VOL	Output LOW Voltage	XC	0.7		V	$I_{OL} = 40\text{ mA}$	$V_{CC} = \text{Min}$ $V_{IN} = V_{IH}$
		XM	0.7			$I_{OL} = 30\text{ mA}$	
		XC, XM	0.4			$I_{OL} = 16\text{ mA}$	
IOH	Output HIGH Current		0.25		mA	$V_{OH} = 30\text{ V}$, $V_{CC} = \text{Min}$ $V_{IN} = V_{IL}$	
ICCH	Power Supply Current		48		mA	$V_{IN} = \text{Gnd}$	$V_{CC} = \text{Max}$
ICCL			51			$V_{IN} = \text{Open}$	
tPLH tPHL	Propagation Delay		15 23		ns	Fig. 3-2, 3-4	

*DC limits apply over operating temperature range; AC limits apply at $T_A = +25^{\circ}\text{C}$ and $V_{CC} = +5.0\text{ V}$.
**OC—Open Collector