

April 1995

**15A, 20A,
400V and 500V N-Channel IGBTs**

Features

- 15A and 20A, 400V and 500V
- $V_{CE(ON)}$ 2.5V
- T_{FI} 1 μ s, 0.5 μ s
- Low On-State Voltage
- Fast Switching Speeds
- High Input Impedance
- No Anti-Parallel Diode

Applications

- Power Supplies
- Motor Drives
- Protection Circuits

Description

The HGTH20N40C1, HGTH20N40E1, HGTH20N50C1, HGTH20N50E1, HGTP15N40C1, HGTP15N40E1, HGTP15N50C1 and HGTP15N50E1 are n-channel enhancement-mode insulated gate bipolar transistors (IGBTs) designed for high-voltage, low on-dissipation applications such as switching regulators and motor drivers. These types can be operated directly from low-power integrated circuits.


PACKAGING AVAILABILITY

PART NUMBER	PACKAGE	BRAND
HGTH20N40C1	TO-218AC	G20N40C1
HGTH20N40E1	TO-218AC	G20N40E1
HGTH20N50C1	TO-218AC	G20N50C1
HGTH20N50E1	TO-218AC	G20N50E1
HGTP15N40C1	TO-220AB	G15N40C1
HGTP15N40E1	TO-220AB	G15N40E1
HGTP15N50C1	TO-220AB	G15N50C1
HGTP15N50E1	TO-220AB	G15N50E1


NOTE: When ordering, use the entire part number.

Packages

HGTH-TYPES JEDEC TO-218AC




HGTP-TYPES JEDEC TO-220AB



Terminal Diagram

N-CHANNEL ENHANCEMENT MODE



Absolute Maximum Ratings $T_C = +25^\circ\text{C}$, Unless Otherwise Specified

	HGTH20N40C1 HGTH20N40E1	HGTH20N50C1 HGTH20N50E1	HGTP15N40C1 HGTP15N40E1	HGTP15N50C1 HGTP15N50E1	UNITS
Collector-Emitter Voltage..... V_{CES}	400	500	400	500	V
Collector-Gate Voltage $R_{GE} = 1M\Omega$ V_{CGR}	400	500	400	500	V
Reverse Collector-Emitter Voltage..... $V_{CES}(\text{rev.})$	-5	-5	-5	-5	V
Gate-Emitter Voltage..... V_{GE}	± 20	± 20	± 20	± 20	V
Collector Current Continuous..... I_C	20	20	15	15	A
Collector Current Pulsed..... I_{CM}	35	35	35	35	A
Power Dissipation at $T_C = +25^\circ\text{C}$ P_D	100	100	75	75	W
Power Dissipation Derating $T_C > +25^\circ\text{C}$	0.8	0.8	0.6	0.6	W/ $^\circ\text{C}$
Operating and Storage Junction Temperature Range... T_J, T_{STG}	-55 to +150	-55 to +150	-55 to +150	-55 to +150	$^\circ\text{C}$

Specifications HGTP15N40C1, 40E1, 50C1, 50E1, HGTH20N40C1, 40E1, 50C1, 50E1

Electrical Specifications $T_C = +25^{\circ}\text{C}$, Unless Otherwise Specified

PARAMETERS	SYMBOL	TEST CONDITIONS	LIMITS				UNITS
			HGTH20N40C1, E1, HGTP15N40C1, E1		HGTH20N50C1, E1, HGTP15N50C1, E1		
			MIN	MAX	MIN	MAX	
Collector-Emitter Breakdown Voltage	BV _{CES}	I _C = 1mA, V _{GE} = 0	400	-	500	-	V
Gate Threshold Voltage	V _{GE(TH)}	V _{GE} = V _{CE} , I _C = 1mA	2.0	4.5	2.0	4.5	V
Zero-Gate Voltage Collector Current	I _{CES}	V _{CE} = 400V, T _C = +25°C	-	250	-	-	μA
		V _{CE} = 500V, T _C = +25°C	-	-	-	250	μA
		V _{CE} = 400V, T _C = +125°C	-	1000	-	-	μA
		V _{CE} = 500V, T _C = +125°C	-	-	-	1000	μA
Gate-Emitter Leakage Current	I _{GES}	V _{GE} = ±20V, V _{CE} = 0	-	100	-	100	nA
Reverse Collector-Emitter Leakage Current	I _{CE}	R _{GE} = 0Ω, V _{EC} = 5V	-	-5	-	-5	mA
Collector-Emitter on Voltage	V _{CE(ON)}	I _C = 20A, V _{GE} = 10V	-	2.5	-	2.5	V
		I _C = 35A, V _{GE} = 20V	-	3.2	-	3.2	V
Gate-Emitter Plateau Voltage	V _{GEP}	I _C = 10A, V _{CE} = 10V	-	6 (Typ)	-	6 (Typ)	V
On-State Gate Charge	Q _{G(ON)}	I _C = 10A, V _{CE} = 10V	-	33 (Typ)	-	33 (Typ)	nC
Turn-On Delay Time	t _{D(ON)I}	I _C = 20A, V _{CE(CL P)} = 300V, L = 25μH, T _J = +100°C, V _{GE} = 10V, R _G = 25Ω	-	50	-	50	ns
Rise Time	t _{RI}		-	50	-	50	ns
Turn-Off Delay Time	t _{D(OFF)I}		-	400	-	400	ns
Fall Time	t _{FI}		-	-	-	-	-
40E1, 50E1			680 (Typ)	1000	680 (Typ)	1000	ns
40C1, 50C1		400	500	400	500	ns	
Turn-Off Energy Loss per Cycle (Off Switching Dissipation = W _{OFF} × Frequency)	W _{OFF}	I _C = 10A, V _{CE(CL P)} = 300V, L = 25μH, T _J = +100°C, V _{GE} = 10V, R _G = 25Ω	1810 (Typ)				μJ
			1070 (Typ)				μJ
Thermal Resistance Junction-to-Case	R _{θJC}	HGTH, HGTM	-	1.25	-	1.25	°C/W
		HGTP	-	1.67	-	1.67	°C/W

INTERSIL CORPORATION IGBT PRODUCT IS COVERED BY ONE OR MORE OF THE FOLLOWING U.S. PATENTS:

4,364,073	4,417,385	4,430,792	4,443,931	4,466,176	4,516,143	4,532,534	4,567,641
4,587,713	4,598,461	4,605,948	4,618,872	4,620,211	4,631,564	4,639,754	4,639,762
4,641,162	4,644,637	4,682,195	4,684,413	4,694,313	4,717,679	4,743,952	4,783,690
4,794,432	4,801,986	4,803,533	4,809,045	4,809,047	4,810,665	4,823,176	4,837,606
4,860,080	4,883,767	4,888,627	4,890,143	4,901,127	4,904,609	4,933,740	4,963,951
4,969,027							

Typical Performance Curves




FIGURE 1. MAX. SWITCHING CURRENT LEVEL. $R_G = 25\Omega$, $V_{GE} = 0\text{V}$ ARE THE MIN. ALLOWABLE VALUES




FIGURE 2. POWER DISSIPATION vs TEMPERATURE DERATING CURVE




FIGURE 3. TYPICAL NORMALIZED GATE THRESHOLD VOLTAGE vs JUNCTION TEMPERATURE




FIGURE 4. TYPICAL TRANSFER CHARACTERISTICS




FIGURE 5. TYPICAL SATURATION CHARACTERISTICS




FIGURE 6. TYPICAL COLLECTOR-TO-EMITTER ON-VOLTAGE vs COLLECTOR CURRENT

Typical Performance Curves (Continued)




FIGURE 7. CAPACITANCE vs COLLECTOR-TO-EMITTER VOLTAGE




FIGURE 8. TYPICAL $V_{CE(ON)}$ vs TEMPERATURE




FIGURE 9. TYPICAL TURN-OFF DELAY TIME




FIGURE 10. TYPICAL INDUCTIVE SWITCHING WAVEFORMS




FIGURE 11. TYPICAL FALL TIME ($I_C = 10\text{A}$)




FIGURE 12. TYPICAL FALL TIME ($I_C = 20\text{A}$)

Typical Performance Curves (Continued)




FIGURE 13. TYPICAL CLAMPED INDUCTIVE TURN-OFF SWITCHING LOSS/CYCLE




FIGURE 14. NORMALIZED SWITCHING WAVEFORMS AT CONSTANT GATE CURRENT. (REFER TO APPLICATION NOTES AN7254 AND AN7260 ON THE USE OF NORMALIZED SWITCHING WAVEFORMS)

Test Circuit




FIGURE 15. INDUCTIVE SWITCHING TEST CIRCUIT

All Intersil semiconductor products are manufactured, assembled and tested under **ISO9000** quality systems certification.

Intersil products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.

For information regarding Intersil Corporation and its products, see web site <http://www.intersil.com>

Sales Office Headquarters

NORTH AMERICA
Intersil Corporation
P. O. Box 883, Mail Stop 53-204
Melbourne, FL 32902
TEL: (407) 724-7000
FAX: (407) 724-7240

EUROPE
Intersil SA
Mercure Center
100, Rue de la Fusée
1130 Brussels, Belgium
TEL: (32) 2.724.2111
FAX: (32) 2.724.22.05

ASIA
Intersil (Taiwan) Ltd.
Taiwan Limited
7F-6, No. 101 Fu Hsing North Road
Taipei, Taiwan
Republic of China
TEL: (886) 2 2716 9310
FAX: (886) 2 2715 3029