

AS OF 2015-01-01 THE PRODUCT IS BLOCKED FOR DELIVERY AND IS NO LONGER AVAILABLE AS A NEW PART. INFORMATION ABOUT SUCCESSOR SEE SIMATIC UPDATE ID: 62977695 FOR FURTHER QUESTIONS PLEASE APPROACH YOUR SIEMENS CONTACT PERSON. SIMATIC MP 277 10" TOUCH MULTI PANEL W. RETENTIVE MEMORY 10,4" TFT DISPLAY 6 MB USER MEMORY CONFIG: WINCC FLEXIBLE 2005 STANDARD SP1



### General information

Customer-specific configuration	Yes
---------------------------------	-----

### Display

Design of display	TFT
Screen diagonal	10.4 in
Number of colors	65 536
Number of grayscales	0
Color type	Colors

### Resolution (pixels)

• Horizontal image resolution	640 Pixel
• Vertical image resolution	480 Pixel
• Resolution (WxH in pixel)	640 x 480

### Backlighting

• MTBF backlighting (at 25 °C)	50 000 h
--------------------------------	----------

### Control elements

Control elements	Touch screen
------------------	--------------

### Keyboard fonts

• Keys with LED	No
-----------------	----

<ul style="list-style-type: none"> <li>• System keys</li> </ul>	No
<ul style="list-style-type: none"> <li>• Numeric/alphabetical input</li> </ul>	Yes / Yes
<ul style="list-style-type: none"> <li>— hexadecimal keyboard</li> </ul>	Yes
<b>Touch operation</b>	
<ul style="list-style-type: none"> <li>• Design as touch screen</li> </ul>	Yes; analog, resistive
<b>Connection type</b>	
<ul style="list-style-type: none"> <li>• Connection for mouse/keyboard/barcode reader</li> </ul>	USB / USB / USB
<b>Installation type/mounting</b>	
Mounting position	vertical
maximum permissible angle of inclination without external ventilation	35°
<b>Supply voltage</b>	
Type of supply voltage	DC
<b>Processor</b>	
Processor type	ARM
<b>Memory</b>	
Type of memory	Flash / RAM
nutzbarer Speicher für Anwenderdaten	6 Mbyte
Main memory	
<ul style="list-style-type: none"> <li>• Capacity of main memory, max.</li> </ul>	128 Mbyte
<b>Time of day</b>	
<b>Clock</b>	
<ul style="list-style-type: none"> <li>• Type</li> </ul>	Hardware clock, battery backup, synchronizable
<ul style="list-style-type: none"> <li>• Hardware clock (real-time clock)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• retentive</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• synchronizable</li> </ul>	Yes
<b>Interfaces</b>	
Interfaces/bus type	1 x RS422, 1 x RS485, 1 x Ethernet (RJ45)
Number of RS 485 interfaces	1
USB port	2 x USB
Multimedia Card slot	1x Multimedia Card slot, up to 128 MB
<b>Industrial Ethernet</b>	
<ul style="list-style-type: none"> <li>• Industrial Ethernet interface</li> </ul>	1 x Ethernet (RJ45)
<b>Protocols</b>	
Supports protocol for PROFINET IO	Yes
PROFIsafe	No
PROFIBUS	Yes
<b>Protocols (Ethernet)</b>	
<ul style="list-style-type: none"> <li>• TCP/IP</li> </ul>	Yes

Further protocols	
• other bus systems	Yes
Degree and class of protection	
Front	IP65, NEMA 4x (when installed)
IP (at the front)	IP65
IP (rear)	IP20
Standards, approvals, certificates	
Certifications	CE, FM Class I Div. 2, UL, cULus, EX Zone 22, NEMA 4x (Enclosure Type 4X, Type 12)
cULus	Yes
Suitable for safety functions	No
Use in hazardous areas	
• EX zone 22	Yes
• FM Class I Division 2	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	50 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	90 %
Operating systems	
Operating system	Windows CE
Configuration	
Message indicator	Yes
Alarm logging system (incl. buffer and acknowledgment)	Yes
Process value display (output)	Yes
Process value default (input) possible	Yes
Recipe administration	Yes
Configuration software	
• STEP 7 Basic (TIA Portal)	No
• STEP 7 Professional (TIA Portal)	No
• WinCC flexible Compact	No
• WinCC flexible Standard	Yes
• WinCC flexible Advanced	Yes
• WinCC Basic (TIA Portal)	No
• WinCC Comfort (TIA Portal)	Yes
• WinCC Advanced (TIA Portal)	Yes

• WinCC Professional (TIA Portal)	Yes
• Configuration tool	WinCC flexible Standard Version 2005 SP1 or higher (to be ordered separately)
• 2. Configuration kit	WinCC flexible Standard
— Version	Version 2005 SP 1
— Configuration tool	WinCC flexible
— Type	Standard

## Languages

Online languages	
• Number of online/runtime languages	16
Project languages	
• Languages per project	32

## Functionality under WinCC (TIA Portal)

Libraries	Yes
Task planner	Yes
Help system	Yes
• Number of characters per info text	80
Message system	
• Number of alarm classes	32
• Number of messages	4 000
• Bit messages	Yes
— Number of bit messages	4 000
• Analog messages	Yes
— Number of analog messages	200
• System messages HMI	Yes
• System messages PLC	Yes
• System messages, other (SIMATIC S7, Sinumerik, Simotion, etc.)	Yes
• Message length (in characters)	80
• Lines	1
• Number of process values per message	8
• Acknowledgment groups	
— Number of acknowledgement groups	Yes
• Message indicator	Yes
• First/last value	Yes
Recipe administration	
• Number of recipes	300
• Data records per recipe	500
• Entries per data record	1 000
• Recipe memory	64 KB integrated Flash, expandable
Variables	

• Number of variables per device	2 048
• Number of variables per screen	200
• Number of variables	1 000
• Limit values	Yes
• Multiplexing	Yes
• Structures	Yes
• Type Date & Time	2 048
<b>Images</b>	
• Number of configurable images	500
• Permanent window/default	Yes
• Start screen configurable	Yes
• Image selection by PLC	Yes
• Image number in the PLC	Yes
<b>Image objects</b>	
• Text objects	10,000 text elements
• Number of I/O fields per image	200
• Number of date/time fields	200
• Return	Yes
• Graphics object	Bit maps, icons, vector graphics
— Icons	1 000
<b>Complex image objects</b>	
• Status/control	With SIMATIC S7
• dynamic objects	Diagrams, bar graphs, sliders, analog display, invisible buttons
— Number of objects per project	1 000
— Number of curve diagrams per image	10
• Methods	Trend / profile
• Limit value lines	Yes
• Number of bars per chart	10
• Limit value lines	Yes
• alphanumeric fields	300
• alphanumeric fields per image	200
• numerical fields	2 048
• numerical fields per image	200
• Password fields	2 048
• Number of slides per image	10
• Number of analog indicators per image	10
• Number of visible switches per project	200
• visible switches per image	200
• hidden switches per image	200
• Number of status switches per project	200
• Anzahl Zustandsschalter pro Bild	200

• Number of selector switches per project	200
• Selector switches per image	200
• Number of decade switches per project	200
• Decade switches per image	200
• Number of signal lamps per project	200
• Signal lamps per image	200
<b>Attributes for dynamic objects</b>	
• Color change	Yes
• X/Y movement	Yes
• Hide	Yes
<b>Lists</b>	
• Number of text lists per project	500
• Number of text lists per image	200
• Number of entries per text list	256
• Number of graphics lists per project	400
• Number of graphic lists per image	200
• Number of entries per graphics list	256
<b>Archiving</b>	
• Number of archives per device	20
• Number of measuring points per project	20
• Number of entries per archive	10 000
• Message archive	Yes
• Process value archive	Yes
• Archiving methods	
— Sequential archive	Yes
— Short-term archive	Yes
• Memory location	SD and MultiMediaCard
• Data storage format	
— CSV	Yes
• Online evaluation	
— using trend curves	Yes
<b>Filters</b>	
• cyclic	Yes
• Tolerance	Yes
• Change	Yes
<b>Security</b>	
• Number of user groups	50
• Number of user rights	32
• Password export/import	Yes
<b>Logging through printer</b>	
• Recording/Printing	Alarms, report (shift report), color print, hardcopy

<b>Transfer (upload/download)</b>	
• Transfer of configuration	MPI/PROFIBUS DP, USB, Ethernet, automatic transfer recognition
<b>Process coupling</b>	
• Connection to controller	S5, S7-200, S7-300/400, TI 505, SINUMERIK, SIMOTION, Allen Bradley (DF1), Allen Bradley (DF485), Mitsubishi (FX), OMRON (LINK/Multilink), Modicon (Modbus) see chapter "System interfaces"
• S7-1200	Yes
• S7-1500	Yes
• S7-200	Yes
— PPI (point-to-point)	Yes
— PPI network	Yes
— MPI	Yes
— PROFIBUS DP	Yes
— Ethernet	Yes
• S7-300/400	Yes
— MPI	Yes
— PROFIBUS DP	Yes
— PROFINET	Yes
• S5	Yes
— PROFIBUS DP	Yes
• TI 505	Yes
• Allen Bradley (DF1)	Yes
• Allen Bradley (DF485)	Yes
• Mitsubishi (FX)	Yes
• Mitsubishi (MP4)	Yes
• Telemecanique (Uni-Telway)	Yes
• OMRON (LINK/Multilink)	Yes
• Modicon (Modbus)	Yes
• GE-Fanuc (SNP)	Yes
<b>Functions</b>	
• TAB sequence	Yes
• Calculating functions	Yes
• Animate	Yes
<b>Service tools/configuration aids</b>	
• Clean screen	Yes
• Touch calibration	Yes
• Backup/Restore manually	Yes
• Simulation	Yes
• Device switchover	Yes
• Delta transfer	Yes

## Expandability/openness

- |                         |     |
|-------------------------|-----|
| • Open Platform Program | Yes |
|-------------------------|-----|

## Peripherals/Options

Peripherals	Printer, barcode reader
• Multimedia Card	Yes
• SD card	Yes
• USB memory	Yes
Additional software components loadable	Yes

## Dimensions

Width of the housing front	335 mm
Height of housing front	275 mm
Mounting cutout, width	310 mm
Mounting cutout, height	248 mm
Overall depth	61 mm

## Weights

Weight (without packaging)	2.65 kg
----------------------------	---------

## Other

free hotline	Yes
Warranty period	1 y
<b>last modified:</b>	13.08.2015