


NEC
ELECTRON DEVICE

MOS FIELD EFFECT TRANSISTOR

2SJ142

FAST SWITCHING
P-CHANNEL SILICON POWER MOS FET



Features

Suitable for switching power supplies,
actuator controls and pulse circuits
4V Gate Drive — Logic Level —
Large current switching : $I_{D(DC)}=13A$
Low $R_{DS(on)}$

No Secondary Breakdown




Absolute Maximum Ratings ($T_a=25^\circ C$)

Drain to Source Voltage	V_{DS}	-100V
Gate to Source Voltage	V_{GS}	$\pm 20V$
Continuous Drain Current	$I_{D(DC)}$	$\pm 13A$
Pulse Drain Current	$I_{D(pulse)}$	$\pm 52A$
Total Power Dissipation	P_T	2.0W
Total Power Dissipation	P_{T*}	35W
Channel Temperature	T_{ch}	150 °C
Storage Temperature	T_{stg}	-55to+150 °C
* $T_{ch} \leq 150^\circ C$		
** $T_c=25^\circ C$		




Electrical Characteristics ($T_a=25^\circ C$)







Characteristics	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Drain Leakage Current	I_{DSS}			- 10	μA	$V_{DS}=-100V, V_{GS}=0$
Gate to Source Leakage Current	I_{GSS}			100	nA	$V_{GS}=20V, V_{DS}=0$
Gate to Source Cutoff Voltage	$V_{GS(off)}$	-1.0		-3.0	V	$V_{DS}=-10V, I_D=-1.0mA$
Forward Transfer Admittance	$ y_{fs} $	5.0			S	$V_{DS}=-10V, I_D=-10A$
Drain to Source On-State Resistance	$R_{DS(on)}$			0.2	Ω	$V_{GS}=-10V, I_D=-10A$
Drain to Source On-State Resistance	$R_{DS(on)}$			0.3	Ω	$V_{GS}=-1.0V, I_D=-3.0A$
Input Capacitance	C_{iss}		3200		pF	$V_{DS}=-10V, V_{GS}=0$
Output Capacitance	C_{oss}		700		pF	$V_{GS}=0, f=1.0MHz$
Reverse Transfer Capacitance	C_{rss}		150		pF	$I_D=-10A, V_{GS(on)}=-10V, V_{GS(off)}=-50V, R_L=5\Omega$
Turn-On Delay Time	$t_{d(on)}$		18		ns	
Rise Time	t_r		100		ns	
Turn-Off Delay Time	$t_{d(off)}$		90		ns	
Fall Time	t_f		100		ns	

TURN-ON AND TURN-OFF TIME TEST CIRCUIT




DERATING FACTOR OF FORWARD BIAS
SAFE OPERATING AREA

FORWARD BIAS SAFE OPERATING AREA

TOTAL POWER DISSIPATION vs.
CASE TEMPERATUREDRAIN CURRENT vs. DRAIN TO
SOURCE VOLTAGE

FORWARD TRANSFER ADMITTANCE
vs. DRAIN CURRENTSOURCE TO DRAIN DIODE
FORWARD VOLTAGECAPACITANCE vs. DRAIN TO
SOURCE VOLTAGEDRAIN TO SOURCE ON-STATE RESISTANCE
vs. GATE TO SOURCE VOLTAGEDRAIN TO SOURCE ON-STATE RESISTANCE
vs. CHANNEL TEMPERATUREDRAIN TO SOURCE ON-STATE RESISTANCE
vs. DRAIN CURRENT

NEC ELECTRON DEVICE



NEC Corporation

INTERNATIONAL ELECTRON DEVICES DIV.
 NEC Building, 33-1, Shiba Gochome
 Minato-ku, Tokyo 108, Japan
 Tel: Tokyo 454-1111
 Telex Address: NECTOK J22686
 Cable Address: MICROPHONE TOKYO