



# SP6850

## Green-Mode PWM Controller

### DESCRIPTION

The SP6850 is the current mode PWM controller with green-mode power-saving operation, to meet the low standby-power needs of low-power SMPS. This green-mode function enables the power supply to easily meet even the strictest power conservation requirements. The functions such as the leading-edge blanking of the current sensing, internal slope compensation and the small package provide the high efficiency / low cost for SMPS power applications. SP6850 is processed by BiCMOS fabrication, that enables reducing the start-up current and the operating current. SP6850 is available by SOT-23-6L / DIP-8P packages.

### APPLICATIONS


- AC/DC Switching Power Adaptor
- Battery Charger
- PC 5V Standby Power.
- Open-Frame Switching Power Supply

### FEATURES


- High-Voltage BiCMOS Process
- Very Low Startup Current (Typ ~ 8 $\mu$ A)
- Under Voltage Lockout (UVLO )
- Current Mode Control with Cycle Peak
- Current Limiting
- Leading-Edge Blanking
- Programmable Switching Frequency
- Internal Slope Compensation
- Green-Mode Control for Power Saving
- Non-audible-noise Green Mode Control
- 300mA Driving Capability
- OVP (Over Voltage Protection) on Vcc Pin

### PIN CONFIGURATION

#### SOT-23-6L




#### DIP-8P



### PART MARKING

#### SOT-23-6L



#### DIP-8P







# SP6850

## Green-Mode PWM Controller

### TYPICAL APPLICATION CIRCUIT



### TYPICAL APPLICATION CIRCUIT ( High Efficiency SMPS + Synchronous Rectifier )





# SP6850

## Green-Mode PWM Controller

### PIN DESCRIPTION


#### SP6850D8TG

| Pin | Symbol | Description                                                                                                                                                                           |
|-----|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1   | OUT    | Gate driver output to drive the external MOSFET                                                                                                                                       |
| 2   | VCC    | Supply Voltage in                                                                                                                                                                     |
| 3   | NC     | Unconnected pin                                                                                                                                                                       |
| 4   | CS     | Current sense. This pin senses the voltage across a resistor, to control PWM output. This pin also provides current amplitude information for current-mode control.                   |
| 5   | RT     | This current is used to charge an internal capacitor, to determine the switching frequency.                                                                                           |
| 6   | NC     | Unconnected pin                                                                                                                                                                       |
| 7   | COMP   | Voltage feedback. The pin provides the output voltage regulation signal., it provides feedback to the internal PWM comparator, so that the PWM comparator can control the duty cycle. |
| 8   | GND    | Ground                                                                                                                                                                                |

#### SP6850S26RG

| Pin | Symbol | Description                                                                                                                                                                          |
|-----|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1   | GND    | Ground                                                                                                                                                                               |
| 2   | COMP   | Voltage feedback. The pin provides the output voltage regulation signal., it provides feedback to the internal PWM comparator, so that the PWM comparator can control the duty cycle |
| 3   | RT     | This current is used to charge an internal capacitor, to determine the switching frequency.                                                                                          |
| 4   | CS     | Current sense. This pin senses the voltage across a resistor, to control PWM output. This pin also provides current amplitude information for current-mode control                   |
| 5   | VCC    | Supply Voltage in                                                                                                                                                                    |
| 6   | OUT    | Gate driver output to drive the external MOSFET                                                                                                                                      |

### BLOCK DIAGRAM





# SP6850

## Green-Mode PWM Controller

### ORDERING INFORMATION

| Part Number  | Package   | Part Marking |
|--------------|-----------|--------------|
| SP6850AD8TG  | DIP-8P    | SP6850I      |
| SP6850BD8TG  | DIP-8P    | SP6850I      |
| SP6850AS26RG | SOT-23-6L | 85AYW        |
| SP6850BS26RG | SOT-23-6L | 850YW        |

※ SP6850AD8TG / SP6850BD8TG : Tube ; Pb – Free

※ SP6850AS26RG / SP6850BS26RG : Tape Reel ; Pb – Free

### ABSOLUTE MAXIMUM RATINGS ( $T_A=25^{\circ}\text{C}$ , unless otherwise specified.)

The following ratings designate persistent limits beyond which damage to the device may occur.

| Symbol           | Parameter                                        | Value      | Unit               |
|------------------|--------------------------------------------------|------------|--------------------|
| $V_{CC}$         | DC Supply Voltage                                | 36         | V                  |
| $V_{COMP/RT/CS}$ | COMP / RT / CS Voltage                           | -0.3 ~ 7.0 | V                  |
| $P_D$            | Power Dissipation @ $T_A=85^{\circ}\text{C}$ (*) | 0.3        | W                  |
| ESD              | Human Body Model                                 | 4          | KV                 |
|                  | Machine Model                                    | 300        | V                  |
| $T_{ope}$        | Operating Ambient Temperature                    | -40 ~ 85   | $^{\circ}\text{C}$ |
| $T_J$            | Operating Junction Temperature Range             | -40 ~ 150  | $^{\circ}\text{C}$ |
| $T_{STG}$        | Storage Temperature Range                        | -40 ~ 150  | $^{\circ}\text{C}$ |
| $T_{LEAD}$       | Pb-Free Lead Soldering Temperature for 5 sec.    | 260        | $^{\circ}\text{C}$ |
| $R_{\theta JC}$  | Thermal Resistance Junction – Case (*)           | SOT-23-6L  | 210                |
|                  |                                                  | DIP-8P     | 95                 |

(\*) The power dissipation and thermal resistance are evaluated under copper board mounted with free air conditions.



# SP6850

## Green-Mode PWM Controller

### ELECTRICAL CHARACTERISTICS

(T<sub>A</sub>=25°C, V<sub>CC</sub>=15V, unless otherwise specified.)


| Symbol                                | Parameter                                            | Conditions                                    | Min. | Typ. | Max. | Unit |
|---------------------------------------|------------------------------------------------------|-----------------------------------------------|------|------|------|------|
| <b>Supply Voltage ( Vcc Pin )</b>     |                                                      |                                               |      |      |      |      |
| I <sub>stt</sub>                      | Startup Current                                      |                                               |      | 8    | 20   | uA   |
| I <sub>op</sub>                       | Operating Current                                    | V <sub>COMP</sub> = 3V                        |      | 2    | 4    | mA   |
| UVLO (off)                            | Min. Operating Voltage                               |                                               | 9.0  | 10.0 | 11.0 | V    |
| UVLO (on )                            | Start Threshold Voltage                              |                                               | 15.0 | 16.0 | 17.0 | V    |
| OVP Level                             | Over Voltage Protection                              |                                               | 28   |      | 36   | V    |
| <b>Voltage Feedback ( Comp Pin )</b>  |                                                      |                                               |      |      |      |      |
| I <sub>sc</sub>                       | Short Circuit Current                                |                                               |      | 2.2  | 3.0  | mA   |
| V <sub>op</sub>                       | Open Loop Voltage                                    |                                               |      | 5.0  |      | V    |
| V <sub>TH(GM)</sub>                   | Green Mode Threshold V <sub>COMP</sub>               |                                               |      | 2.35 |      | V    |
| <b>Oscillator ( RT Pin )</b>          |                                                      |                                               |      |      |      |      |
| F <sub>osc</sub>                      | Frequency                                            | R <sub>T</sub> =100KΩ                         | 60.0 | 65.0 | 75.0 | KHz  |
| F <sub>osc(GM)</sub>                  | Green Mode Frequency                                 | F <sub>s</sub> =65.0KHz                       |      | 20   |      | KHz  |
| F <sub>dt</sub>                       | Frequency Variation versus Temp. Deviation           | (-40°C ~105°C)                                |      |      | 3    | %    |
| F <sub>dv</sub>                       | Frequency Variation versus V <sub>CC</sub> Deviation | (V <sub>CC</sub> =11V-25V)                    |      |      | 1    | %    |
| <b>Current Sensing ( CS Pin )</b>     |                                                      |                                               |      |      |      |      |
| V <sub>cs(off)</sub>                  | Maximum Input Voltage                                | SP6850BD8TG<br>SP6850BS26RG                   | 0.8  | 0.85 | 0.9  | V    |
|                                       |                                                      | SP6850AD8TG<br>SP6850AS26RG                   | 0.7  | 0.75 | 0.8  |      |
| Z <sub>cs</sub>                       | Input impedance                                      |                                               |      | 50   |      | KΩ   |
| T <sub>PD</sub>                       | Delay to Output                                      |                                               |      | 150  |      | nS   |
| <b>Gate Driver Output ( OUT Pin )</b> |                                                      |                                               |      |      |      |      |
| DC (Max)                              | Maximum Duty Cycle                                   |                                               | 70   | 75   | 80   | %    |
| DC (Min)                              | Minimum Duty Cycle                                   |                                               |      | 0    |      | %    |
| V <sub>OL</sub>                       | Output Low Level                                     | V <sub>CC</sub> =15V,<br>I <sub>O</sub> =20mA |      |      | 1    | V    |
| V <sub>OH</sub>                       | Output High Level                                    | V <sub>CC</sub> =15V,<br>I <sub>O</sub> =20mA | 8    |      |      | V    |
| T <sub>r</sub>                        | Rising Time                                          | Load Cap=1000pF                               |      | 50   | 200  | nS   |
| T <sub>f</sub>                        | Falling Time                                         | Load Cap=1000pF                               |      | 30   | 120  | nS   |




# SP6850

## Green-Mode PWM Controller


PERFORMANCE CHARACTERISTICS ( $T_A=25^\circ\text{C}$ , unless otherwise specified.)




Startup Current (I<sub>startup</sub>) vs. Temperature



V<sub>COMP</sub> open loop voltage v.s. Temperature



UVLO (On) vs. Temperature




UVLO Off v.s. Temperature




# SP6850

## Green-Mode PWM Controller


PERFORMANCE CHARACTERISTICS ( $T_A=25^{\circ}\text{C}$ , unless otherwise specified.)




Frequency v.s. Temperature



Green Mode Frequency v.s. Temperature



Frequency v.s.  $V_{CC}$




Green mode frequency v.s.  $V_{CC}$



# SP6850

## Green-Mode PWM Controller

### DIP- 8P PACKAGE OUTLINE




| Symbol | Dimensions In Millimeters |       | Dimensions In Inches |       |
|--------|---------------------------|-------|----------------------|-------|
|        | Min                       | Max   | Min                  | Max   |
| A      | 3.710                     | 4.310 | 0.146                | 0.170 |
| A1     | 0.510                     |       | 0.020                |       |
| A2     | 3.200                     | 3.600 | 0.126                | 0.142 |
| B      | 0.380                     | 0.570 | 0.015                | 0.022 |
| B1     | 1.524 (BSC)               |       | 0.060 (BSC)          |       |
| C      | 0.204                     | 0.360 | 0.008                | 0.014 |
| D      | 9.000                     | 9.400 | 0.354                | 0.370 |
| E      | 6.200                     | 6.600 | 0.244                | 0.260 |
| E1     | 7.320                     | 7.920 | 0.288                | 0.312 |
| e      | 2.540 (BSC)               |       | 0.100 (BSC)          |       |
| L      | 3.000                     | 3.600 | 0.118                | 0.142 |
| E2     | 8.400                     | 9.000 | 0.331                | 0.354 |



# SP6850

## Green-Mode PWM Controller

### SOT-23-6L PACKAGE OUTLINE



| Symbol | Dimensions In Millimeters |       | Dimensions In Inches |       |
|--------|---------------------------|-------|----------------------|-------|
|        | Min                       | Max   | Min                  | Max   |
| A      | 1.050                     | 1.250 | 0.041                | 0.049 |
| A1     | 0.000                     | 0.100 | 0.000                | 0.004 |
| A2     | 1.050                     | 1.150 | 0.041                | 0.045 |
| b      | 0.300                     | 0.400 | 0.012                | 0.016 |
| c      | 0.100                     | 0.200 | 0.004                | 0.008 |
| D      | 2.820                     | 3.020 | 0.111                | 0.119 |
| E      | 1.500                     | 1.700 | 0.059                | 0.067 |
| E1     | 2.650                     | 2.950 | 0.104                | 0.116 |
| e      | 0.950TYP                  |       | 0.037TYP             |       |
| e1     | 1.800                     | 2.000 | 0.071                | 0.079 |
| L      | 0.700REF                  |       | 0.028REF             |       |
| L1     | 0.300                     | 0.600 | 0.012                | 0.024 |
| θ      | 0°                        | 8°    | 0°                   | 8°    |



# SP6850

## Green-Mode PWM Controller

---

Information provided is alleged to be exact and consistent. SYNC Power Corporation presumes no responsibility for the penalties of use of such information or for any violation of patents or other rights of third parties that may result from its use. No license is granted by allegation or otherwise under any patent or patent rights of SYNC Power Corporation. Conditions mentioned in this publication are subject to change without notice. This publication surpasses and replaces all information previously supplied. SYNC Power Corporation products are not authorized for use as critical components in life support devices or systems without express written approval of SYNC Power Corporation.

©The SYNC Power logo is a registered trademark of SYNC Power Corporation  
©2004 SYNC Power Corporation – Printed in Taiwan – All Rights Reserved  
SYNC Power Corporation  
9F-5, No.3-2, Park Street  
NanKang District (NKSP), Taipei, Taiwan, 115, R.O.C  
Phone: 886-2-2655-8178  
Fax: 886-2-2655-8468  
<http://www.syncpower.com>