# SIEMENS

### Hall-Effect Vane Switch

#### Features

- Contactless switch with open collector output (40 mA)
- Static switching
- High switching frequency
- Hermetically sealed with plastic
- Unaffected by dirt, light, vibration
- Large temperature and voltage range
- Integrated overvoltage protection
- High interference immunity
- Integrated capacitors for EMI protection



Туре	Ordering Code	Package		
HKZ 121	Q67000-A9097-A401	P-HKZ-3-1		

The Hall-effect vane switch HKZ 121 is a contactless switch consisting of a monolithic integrated Hall-effect circuit and a special magnetic circuit hermetically sealed in a plastic package. The switch is actuated by a soft-iron vane which is passed through the air gap between magnet and Hall sensor.

The main application field is in cars, i.e. as a breakerless trigger in electronic ignition systems. Numerous industrial applications can be found in control engineering, especially in those areas where switches must operate maintenance-free under harsh environmental conditions (e.g. rpm sensor, limit switch, position sensor, speed measurement, shaft encoder, scanning of coding disks, etc.).

#### HKZ 121

**Bipolar IC** 

## SIEMENS

#### Function

The Hall-effect switch is actuated by a soft-iron vane that passes through the air gap between magnet and Hall-effect sensor. The vane short-circuits the magnetic flux before the hall-effect sensor, as shown below. The open collector output is conductive (low) when the vane is outside the air gap, and blocks (high) when the vane is introduced into the air gap. The output remains high as long as the vane remains in the air gap. This static function does not require a minimum operating frequency. The output signal shape is independent of the operating frequency.

The circuit features integrated overvoltage protection against most of the voltage peaks occurring in automotive and industrial applications. The output stage has a Schmitt trigger characteristic. Most electronic circuits can be driven directly due to the open collector output current of max. 40 mA.



#### **Principle of Operation**

#### **Mechanical Characteristics**

The Hall-effect vane switch is hermetically sealed in a special plastic package, so that it can also be used under harsh environmental conditions. The package is waterproof, vibration-resistant and resistant to gasoline, oil and salt. Two tubular rivets are incorporated in the package to mount the sensor on its carrier plate. The circuit has three flexible leads for power supply, output and ground.

#### **Application Notes**

The output current of the "open collector" must be limited to the maximum permissible value by a load resistor adapted to the application.

For optimum efficiency of the integrated overvoltage protection, it is suggested that a resistor of approx. 100  $\Omega$  be provided in the component's power supply to limit the current.

#### Absolute Maximum Ratings

Parameter	Symbol	Limit Values		Unit	Test Condition
		min.	max.		
Supply voltage	Vs	- 1.2	24 30	V V	_ T <sub>A</sub> = 25 °C
Output voltage in OFF-state	VQ	- 0.8	30	V	_
Inverse supply current (limited externally) Output current	- Is Iq	-	200 40	mA mA	$T_{A} \le 80 \ ^{\circ}C$ $t \le 1 \ h$ without vane
Inverse output current	- <i>I</i> Q	_	30	mA	
Ambient temperature Storage temperature	TA Tstg	- 40 - 40	135 150	С° С	
Thermal resistance system - air	$R_{ m th}$ SA	_	170	K/W	_

#### **Operating Range**

Supply voltage	Vs	4.5	24	V	-
Ambient temperature	TA	- 40	130	°C	-
Vane <sup>1)</sup> : thickness width gap length immersion depth gap height	a b c h d	0.5 8 8 4.6 7.3 – h	9	mm mm mm mm	- - - -

#### **Characteristics**

 $V_{\rm S} = 5 \text{ V to } 18 \text{ V}, T_{\rm A} = -30 \text{ to } 130 \text{ }^{\circ}\text{C}$ 

Parameter	Symbol	Limit Values		Unit	Test Condition
		min.	max.		
Output saturation voltage	V <sub>Q</sub> sat	-	- - 0.4 0.6	- - V V	without vane $I_{Q} = 40 \text{ mA}$ $T_{A} = -30 \text{ to } 110 \text{ °C}$ $T_{A} = 110 \text{ to } 130 \text{ °C}$
Output reverse current Supply current	Iqr Is	-	10 12	μA mA	with vane without vane
Fall time	<i>t</i> HL	_	1	μS	<i>I</i> <sub>Q</sub> = 40 mA
Overvoltage protection – Supply voltage (Vs) – Output (Va)	Vsz Vso	32 32	42 42	V V	<i>I</i> s = 16 mA <i>I</i> s = 16 mA

#### **Switching Point Characteristics**

#### Definitions

In most applications, the switching point is set exactly by mechanical adjustment, thus compensating all mechanical tolerances in the system including the scatter of the Hall-effect vane switch. For the function of the device in operation, only the deviations of those characteristics are important on temperature and operating voltage.

The characteristic values of the switching points are, therefore, not directly referred to the mechanical dimensions of the vane switch, but to an electrically defined symmetry  $B_0$  according to formula 1):

1) 
$$B_0 = (ON_{left} + OFF_{left} + ON_{right} + OFF_{right})$$
: 4  
 $B_0 = A_0 \pm 0.3 \text{ mm}$ 

The definition of the operate and release points is shown the following figure.

Operate point  $f_{ON}$  is obtained by subtracting the measured ON operate value from the reference point B<sub>0</sub>:

2) 
$$f_{ON} = ON_{right} - B_0 = B_0 - ON_{left}$$

The release point *f*<sub>OFF</sub> is calculated from the difference between the appropriate ON and OFF points:

3)  $f_{OFF} = ON_{right} - OFF_{right} = OFF_{left} - ON_{left}$ 

 $f_{ON 0}$  and  $f_{OFF 0}$  are the switching points measured for the individual component under normal conditions ( $V_S = 12 \text{ V}$ ,  $T_A = 25 \text{ °C}$ ) within the characteristic device deviation.

The deviations of the operate and release points are defined according to 4):

4)  $\Delta f \circ n = f \circ n - f \circ n \circ$  $\Delta f \circ f = f \circ f - f \circ f \circ f \circ$ 

### SIEMENS



**Switching Point Definitions** 

![](_page_5_Figure_2.jpeg)

#### **Mechanical Measurement Conditions**

#### **Switching Point Characteristics**

Vane: a = 0.75 mm, b = 8 mm, c = 10 mm Position: center of air gap  $V_{\rm S} = 5$  V to 18 V

Parameter	Symbol	Limit Values			Unit	Test Condition
		min.	typ.	max.		
HKZ 121						
Operate point	<b>f</b> on 0	0.85	1.45	2.05	mm	$V_{\rm S} = 12 \text{ V}, T_{\rm A} = 25 \text{ °C}$
Deviations	$\Delta f_{ON}$	- 0.4	0.15	0.7	mm	$T_{\rm A} = -30$ to 25 °C
		- 0.2	0.15	0.4	mm	<i>T</i> <sub>A</sub> = 25 to 80 °C
		- 0.4	0.2	0.7	mm	<i>T</i> <sub>A</sub> = 80 to 130 °C
Release point	foff 0	1.54	2.54	3.54	mm	<i>V</i> s = 12 V, <i>T</i> <sub>A</sub> = 25 °C
Deviations	$\Delta f_{\text{OFF}}$	- 0.8	0.3	1.4	mm	$T_{\rm A} = -30$ to 25 °C
		- 0.4	0.3	0.8	mm	<i>T</i> <sub>A</sub> = 25 to 80 °C
		- 0.8	0.4	1.4	mm	<i>T</i> <sub>A</sub> = 80 to 130 °C

#### Package Outlines

![](_page_6_Figure_3.jpeg)

Dimensions in mm

This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.