

# SOT223 N-CHANNEL ENHANCEMENT MODE VERTICAL DMOS FET


## ZVN2106G

ISSUE 3 – NOVEMBER 1995

### FEATURES

- \* 60 Volt  $V_{DS}$
- \*  $R_{DS(on)}=2\Omega$

COMPLEMENTARY TYPE - ZVP2106G  
PARTMARKING DETAIL - ZVN2106



### ABSOLUTE MAXIMUM RATINGS.

| PARAMETER                                         | SYMBOL         | VALUE       | UNIT        |
|---------------------------------------------------|----------------|-------------|-------------|
| Drain-Source Voltage                              | $V_{DS}$       | 60          | V           |
| Continuous Drain Current at $T_{amb}=25^{\circ}C$ | $I_D$          | 710         | mA          |
| Pulsed Drain Current                              | $I_{DM}$       | 8           | A           |
| Gate Source Voltage                               | $V_{GS}$       | $\pm 20$    | V           |
| Power Dissipation at $T_{amb}=25^{\circ}C$        | $P_{tot}$      | 2.0         | W           |
| Operating and Storage Temperature Range           | $T_j; T_{stg}$ | -55 to +150 | $^{\circ}C$ |

### ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}C$ unless otherwise stated).

| PARAMETER                                   | SYMBOL       | MIN. | MAX.       | UNIT          | CONDITIONS.                                                               |
|---------------------------------------------|--------------|------|------------|---------------|---------------------------------------------------------------------------|
| Drain-Source Breakdown Voltage              | $BV_{DSS}$   | 60   |            | V             | $I_D=1mA, V_{GS}=0V$                                                      |
| Gate-Source Threshold Voltage               | $V_{GS(th)}$ | 0.8  | 2.4        | V             | $I_D=1mA, V_{DS}=V_{GS}$                                                  |
| Gate-Body Leakage                           | $I_{GSS}$    |      | 20         | nA            | $V_{GS}=\pm 20V, V_{DS}=0V$                                               |
| Zero Gate Voltage Drain Current             | $I_{DSS}$    |      | 500<br>100 | nA<br>$\mu A$ | $V_{DS}=60V, V_{GS}=0$<br>$V_{DS}=48V, V_{GS}=0V,$<br>$T=125^{\circ}C(2)$ |
| On-State Drain Current (1)                  | $I_{D(on)}$  | 2    |            | A             | $V_{DS}=18V, V_{GS}=10V$                                                  |
| Static Drain-Source On-State Resistance (1) | $R_{DS(on)}$ |      | 2          | $\Omega$      | $V_{GS}=10V, I_D=1A$                                                      |
| Forward Transconductance (1)(2)             | $g_{fs}$     | 300  |            | mS            | $V_{DS}=18V, I_D=1A$                                                      |
| Input Capacitance (2)                       | $C_{iss}$    |      | 75         | pF            | $V_{DS}=18V, V_{GS}=0V, f=1MHz$                                           |
| Common Source Output Capacitance (2)        | $C_{oss}$    |      | 45         | pF            |                                                                           |
| Reverse Transfer Capacitance(2)             | $C_{rss}$    |      | 20         | pF            |                                                                           |
| Turn-On Delay Time (2)(3)                   | $t_{d(on)}$  |      | 7          | ns            | $V_{DD} \approx 18V, I_D=1A$                                              |
| Rise Time (2)(3)                            | $t_r$        |      | 8          | ns            |                                                                           |
| Turn-Off Delay Time (2)(3)                  | $t_{d(off)}$ |      | 12         | ns            |                                                                           |
| Fall Time (2)(3)                            | $t_f$        |      | 15         | ns            |                                                                           |

(1) Measured under pulsed conditions. Width=300 $\mu s$ . Duty cycle  $\leq 2\%$  (2) Sample test.

(3) Switching times measured with 50 $\Omega$  source impedance and <5ns rise time on a pulse generator  
Spice parameter data is available upon request for this device

# ZVN2106G

## TYPICAL CHARACTERISTICS

